

SPE-PBM30

Retail \$ 276.00 CCW Price: \$ 179.40



30W Contractor Series PA Amplifier

UL Listed. Our two channel contractor series mixer/amplifier is a 30 watt amplifier. It features an auto mute function, music on hold output with separate level control (600 ohm line and one watt 8 ohm), 600 ohm telephone line input with level control, bass/treble to our two channel contractor series mixer/amplifier is a 30 watt amplifier. It features an auto mute function, music on hold output with separate level control (600 ohm line and one watt 8 ohm), 600 ohm telephone line input with level control, bass/treble tone controls, front panel level controls, and manual muting contacts. In addition to the telephone line input, this unit accepts inputs from two sound sources. Each source utilizes a microphone input (terminal strip). Source 1 also offers the option of an auto summing stereo auxiliary RCA input. Outputs include a choice of 4, 8, and 16 ohm as well as 70 and 25 volt line outputs. Rack (PBM-RK1) and wall (PBM-WK1) mounting kits are available (not included).

Technical Specifications

Finish	Black
Frequency Response Rate	50-15,000 Hz. +/- 3 dB
Input Sensitivity/Impedance	Tel: 100mV/600 ohms, unbalanced, Mic-1-2: 1.0mV/600 ohms, balanced, Aux- 1: 200mV/50,000 ohms, unbalanced

SPE-PBM30

Music on Hold	600 ohm line/1 Volt, 8 ohm/ 1 Watt
Mute Level	Aux 1/Mic 2 \geq 40 dB
Power Supply	120 VAC, 50/60 Hz.
Rated Output Power	30 W RMS
S/N Ratio	Mic- 1-2: Better than 55 dB, Aux- 1: Better than 70 dB, Tel: Better than 60 dB
Speaker Outputs	4 ohms, 8 ohms, 16 ohms, 25/70V line
Tone Controls	Bass +/- 10 dB at 100 Hz. Treble +/- 10 dB at 100 Hz.
Total Harmonic Distortion	1% or less at 1 kHz.
VOX Level	Mic 1/Tel 0-40 dB adjustable